
## FORD **TRUCKS** 1848T LOW LINER **EURO**6





	5975			
Basic Features				
Vehicle Type	Tractor-Lowliner			
Axle	4x2			
Emission	Euro 6			
Cabin Type	Extra High Roof Sleeper Cab			
Wheelbase (mm)	3600			
Engine				
Type	Ecotorq 12,7 lt			
Displacement (cc)	12740			
Diameter x Stroke	130 mm x 160 mm			
Power	480 PS (353 kW) / 1800 rpm			
Torque	2500 Nm / 1000 - 1200 rpm			
Compression Ratio	17 +/- 0,5 : 1			
Oil Filling Volume	50 L			
Coolant Volume	57 L (77 L with Intarder)			
Transmission				
Clutch	430mm Single Disc			
Automated Transmission	ZF 12 TX 2620 (16,688-1)			
Steering				
	Power Assisted Single Circuit			
Chassis				
Chassis Thickness (mm)	10 mm			
Chassis Strength (MPa)	500 MPa			
Suspension (Front/Rear)	90 mm Parabolic Leaf Springs / Air Suspension			
Axle	Single Reduction			

Chassis				
Chassis Thickness (mm)	10 mm			
Chassis Strength (MPa)	500 MPa			
Suspension (Front/Rear)	90 mm Parabolic Leaf Springs / Air Suspension			
Axle	Single Reduction			
Axle Ratio	2,47			
Tyres (Front/Rear)	315/60 R22.5 / 295/60 R22.5			
Wheel Rim	22,5 x 9 Steel			
Braking System				
Brakes (Front/Rear) (Ø.mm x mm. Length)	430 x 45 - Disc Brakes			
Braking System	Dual Brake Circuit - Air Processing Unit with Integrated Oil Seperator and Heater			
Engine Brake Power	max. 320 kW (Engine Level)			
Intarder Power	max. 600 kW / continuous 160 kW			
Electrical System				
Battery	24V, 2 x 12V 225 Ah			
Alternator / Starter Motor	130 A / 6,5 kW			
Tanks				
Fuel Tank	510 L + 410 L Aluminium			
SCR Tank	55 L			



Dimensions (mm)			
5 <sup>th</sup> Wheel Height		980	
Front Overhang		1500	
Wheelbase		3600	
Overall Length		5975	
Overall Cab Length		2312	
Total Height		3895 (Extra High Roof); 2931 (Low Roof)	
Overall Vehicle Width (Excluding Mirrors)		2541	
Chassis Width		866	
Rear Overhang		875	
Chassis Height-Front		867	
Chassis Height-Rear		842	
Ground Clearance-Front		243	
Ground Clearance-Rear		172	
Turning Radius		7500	
Weights (kg)	1. Axle	2. Axle	Total
Technically Permissible Weights	7100	11500	18000
Kerb Weight	5617	2316	7933
Payload	1483	9184	10067
GVM (Legal )	7100	11500	18000

## STANDARD EQUIPMENT

- Air Conditioner
- Radio/CD Player
- Extra High Roof Cab with Double Bed
- Dry Type Cab Heater
- Air Suspended Cab
- Power Cab Tilting
- Cruise Control
- Engine Brake
- Electrically Operated Windows
- Electrically Operated and Heated Side Mirrors
- Electrically Operated Headlamp Leveling
- Rake and Reach Adjustable Steering Column
- Heated and Air Suspended Driver Seat
- Lumbar Support
- Electrically Operated Sunroof
- Front and Rear Vehicle Antiroll Bar
- Disc Brakes
- Automated Transmission (with Different Usage Modes)
- Electronic Brake System (EBS) and Anti-Lock Brake System (ABS)
- Active Emergency Brake System (AEBS)
- Electronic Brake Force Control
- Brake Assistant
- Electronic Stability Program (ESP)
- Brake Lining Wear Sensor
- Lane Departure Warning System (LDWS)
- Auto Light Sensor
- Rain Sensor
- Immobilizer
- Single Key with Remote Control and Central Locking
- Home Safe Light
- Approach Light
- Differential Lock
- Digital Tachograph
- Switchable Air Compressor for Improved Fuel Economy
- Variable Steering Pump for Improved Fuel Economy
- Hill Launch Assist
- Coupling Force Control
- Front Fog Lamps
- Spoiler \*
- Axle Load Indicator

## **OPTIONAL EQUIPMENT**

- Intarder
- ADR Pack
- Low Roof Sleeper Cab with Single Bed
- Wet Type Cabin Heater
- Cold Pack with Wet Type Cab Heater
- Cold Pack with Dry & Wet Type Cab Heater
- Engine Driven PTO & Interior Control Unit
- Transmission PTO & Interior Control Unit

<sup>\*</sup> Not Available with Low Roof Sleeper Cab Version