

Technical Features

F-LINE 8X2-6X4 Road Series



Technical Features September 2024

Technical Features	3233S	3242S	3542			
Engine	High Roof Sleeper Cab	High Roof Sleeper Cab	Day Cab	Low Roof Sleeper Cab		
Туре	GEN1.5 Ecotorq Euro 6 115 mm x 144 mm	GEN1.5 Ecotorq Euro 6 130 mm x 160 mm	GEN1.5 Ecotorq Euro 6 130 mm x 160 mm	GEN1.5 Ecotorq Euro 6 130 mm x 160 mm		
Displacement (cc)	8.974 cm3	12.740 cm3	12.740 cm3	12.740 cm3		
Power PS (kW)	330 PS (243 kW) @ 1900 d/d	420 PS (308,9 kW) / 1800 d/d	420 PS (309 kW) @ 1800 d/d	420 PS (309 kW) @ 1800 d/d		
Torque	1400 Nm @ 1200-1650 d/d	2150 Nm @ 1000-1300 d/d	2150 Nm @ 1000-1300 d/d	2150 Nm @ 1000-1300 d/d		
Powertrain						
Clutch	430 mm Single Disc	430 mm Single Disc	430 mm Single Disc	430 mm Single Disc		
Transmission / Ratios	Automated: ZF 9S 14409 (9,48 - 0,75) Manual: Eaton 9S 13209 (9,40 - 0,75)	Automated: Ecotorq 16S 2600 DD (17,03 - 1,00)	Automated: Ecotorq 16S 2600 OD (14,107 - 0,823) Manual: ZF 16S 2530 (13,805-0,836)	Automated: Ecotorq 16S 2600 OD (14,107 - 0,823) Manual: ZF 16S 2530 (13,805-0,836)		
Forward and Reverse Gear	Automated: 9 forward + 1 reverse Manual: 9 forward + 1 reverse	Automated: 16 forward + 2 reverse	Automated: 16 forward + 2 reverse Manual: 16 forward + 2 reverse	Automated: 16 forward + 2 reverse Manual: 16 forward + 2 reverse		
FDR	4,63	2,64	4,08	4,08		
Axle & Suspension						
Axle Configuration	8x2	8x2	6x4	6x4		
Front Axle	7 T	7 T	8 T	8 T		
Rear Axle	XSS-510, 13.5 T	XSS-510, 13.5 T	XPT-330, 16 T	XPT-330, 16 T		
Suspension	Parabolic Front Leaf Spring / Compensating Mechanical Rear Suspension	Parabolic Front Leaf Spring / Compensating Mechanical Rear Suspension	Parabolic Front Leaf Spring / Mechanical Rear Suspension	Parabolic Front Leaf Spring / Mechanical Rear Suspension		
Brakes						
Brake System	Dual Brake Circuit - Air Processing Unit with Integrated Oil Seperator and Heater	Dual Brake Circuit - Air Processing Unit with Integrated Oil Seperator and Heater	Dual Brake Circuit - Air Processing Unit with Integrated Oil Seperator and Heater	Dual Brake Circuit - Air Processing Unit with Integrated Oil Seperator and Heater		
Service Brake	Front and Rear Disc Brakes	Front and Rear Disc Brakes	Front and Rear Z-Cam Drum Brake System	Front and Rear Z-Cam Drum Brake System		
Brakes (Front/Rear) (Ø.mm x mm. Length)	430 x 45 - Disc Brake	430 x 45 Disc Brake	410 x 200 Z-Cam Drum Brake System	410 x 200 Z-Cam Drum Brake System		
Engine Brake Power	max. 220 kW (Engine Level)	max. 320 kW (Engine Level)	max. 320 kW (Engine Level)	max. 320 kW (Engine Level)		
Hydraulic Retarder	-	max. 450 kW / continuous 160 kW	max. 450 kW / continuous 160 kW	-		
Fuel & AdBlue Tank						
Fuel Tank	550 L, Right Hand Side, A l uminum	550 L, Right Hand Side, Aluminum	315 L, Right Hand Side, Steel	315 L, Right Hand Side, Steel		
SCR Tank	78 L	78 L	55 L	55 L		
Chassis						
Thickness and Material	U Profile, High Strength, 7 mm Thickness	U Profile, High Strength, 7 mm Thickness	U Profile, High Strength, 7 mm Thickness	U Profile, High Strength, 7 mm Thickness		
Tires						
Front Axle	315/80 R 22,5	315/80 R 22,5	315/80 R 22,5	315/80 R 22,5		
Rear Axle	315/80 R 22,5	315/80 R 22,5	315/80 R 22,5	315/80 R 22,5		
Rims	22.5X9.0 Steel	22.5X9.0 Steel	22.5X9.0 Steel	22.5X9.0 Steel		

Standard and Optional Features

September 2024


Standard and Optional Features	3233S	32 42 S	3542		
Safety & Technology	High Roof Sleeper Cab	High Roof Sleeper Cab	Day Cab	Low Roof Sleeper Cab	
Pre-Collision Assist	•	•	-	-	
Lane Keeping Alert (LDWS)	•	•	•	•	
Pre-Collision Assist	•	•	-	-	
Lane Keeping Alert (LDWS)	•	•	•	•	
Electronic Stability Program (ESP)	•	•	•	•	
Driver Alert System	•	•	•	•	
Moving-off Information System (MOIS)	•	•	•	•	
Rear View Camera	•	•	•	•	
Blind Spot Information System (BLIS)	•	•	•	•	
Alcohol Interlock Facilitation	•	•	•	•	
Traffic Sign Recognition	•	•	•	•	
Emergency Stop Signal	•	•	•	•	
Tire Pressure Monitoring System (TPMS)	•	•	•	•	
Auto High Beam Headlamps	0	0	-	-	
Pre-Collision Assist with Pedestrian Detection	0	0	-	-	
Intelligent Adaptive Cruise Control with Stop & Go (iACC)	-	-	0	0	
Electronic Brake System with ABS & ATC (EBS)	•	•	0	0	
Retarder	-	0	0	-	
Diferential Lock	•	•	•	•	
Interior					
Multimedia System with 9" Touch Screen (DAB Radio, Bluetooth, USB (A Type - C Type), Apple CarPlay, Android Auto, Remote Control)	•	•	•	•	
Navigation	0	0	0	0	
Improved Sound and Heat Insulation	•	•	•	•	
Air Conditioning	•	•	•	•	
Dry & Wet Type Cab Heater	0	0	-		
Dry Type Cab Heater	•	•	-	-	
Wet Type Cab Heater	0	0	0	-	
Dual Passenger Seat	-	1	0	-	
Driver Seat Armrest	•	•	0	•	
Axle Load Measurement Device	•	•	•	•	
Adjustable Steering Wheel	•	•	•	•	
Driver Seatbelt Warning System	•	•	•	•	
Double Bed and Upper Storage Area	0	0	•	•	
Single Bed (Without Upper Storage Areas)	•	•	-	•	
Power Windows & Remote Height Adjustment	•	•	•	•	
Side Window Dimmings	•	•	•	•	
Bed Side Remote Control System	•	•	-	•	
Interior Lighting with Reading and Night Light Functions	•	•	-	•	
Multi-Function Remote Control Key, 2 pieces	•	•	•	•	

Standard and Optional Features	3233S	3242S	3542		
Exterior	High Roof Sleeper Cab	High Roof Sleeper Cab	Day Cab	Low Roof Sleeper Cab	
Heated and Electrically Controlled Side Mirrors	•	•	•	•	
Spoiler & Side Extender	0	0	•	-	
250L Steel Fuel Tank (Left Side)	0	0	•	-	
5900 mm Wheelbase	0	0	•	-	
8 Ton Front Axle Capacity	0	0	•	•	
3,08 FDR	-	0	-	-	
Engine PTO	0	0	0	0	
Twin PTO (Low and High Ratio)	0	0	0	0	
NH1B Transmission PTO	0	0	0	0	
NH1C Transmission PTO	0	0	0	0	
NH4B Transmission PTO	0	0	0	0	
NH4C Transmission PTO	0	0	0	0	
Hydraulic Cab Tilting	•	•	•	•	
Electrically Operated Cab Tilting	0	0	0	0	
FL, EX/II, OX & AT classification ADR Package	0	0	0	0	
Without Front Spare Tire	0	0	0	٥	
Front Spare Tire / Rim	•	•	•	•	
LED Headlamps	0	0	0	0	
Halogen Headlamps	•	•	•	•	
Rain Sensor & Autolamps	•	•	•	•	
Adaptive Cruise Control (ACC)	-	0	-	-	
225 aH Battery	•	•	•	•	
Full Trailer - O3 (up to 10T towing capability)	-	-	0	0	
Full Trailer - O4 (more than 10T towing capability)	-	-	0	0	
Switchable Air Brake Compressor	•	-	0	•	
Smart Tachograph	•	•	0	•	
Short Bumper	-	-	0	•	
Medium Bumper	•	•	0	=	
Air Cab Suspension	-	0	0	=	
Cold Pack	0	0	0	0	
Front Towing Hooks	•	•	0	=	
Beacon Lamp	-	-	0	=	
Double Roof Beacon Lamp (Passenger Side Lamp & Driver Side Infrastructure)	-	-	0	0	

[•] Standard o Optional

Technical Measurements

September 2024







Dimensions (mm)	3233S	32428	35	642
	High Roof Sleeper Cab	High Roof S l eeper Cab	Day Cab	Low Roof Sleeper Cab
Wheelbase (B&C)	5200	5200	4500	4500
Overall Length (G)	9893	10920	9174	9174
Front Overhang (A)	1450	1440	1450	1450
Rear Overhang (F)	1924	2770	1874	1874
Distance Between 1st and 2nd Wheel Centers (B)	3779	3790	4500	4500
Distance Between 2nd and 3th Wheel Centers (C)	1421	1410	1350	1350
Distance Between 3th and 4th Wheel Centers (E)	1319	1330	-	-
Overall Vehicle Width (Excluding Mirrors) (J)	2540	2540	2540	2540
Overall Cab Length (I)	2517	2255	1777	2260
Total Vehicle Height (H)	3109	3906	3127	3127
Turning Radius	-	-	10730	10730

	Weights (kg)	1st Axle	2nd Axle	3rd Axle	4th Axle	Total
3233S	Technically Permissible Weight	7100	7100	12000	8700	33000
	Kerb Weight	5319	1440	1926	1312	9995
(High Roof Sleeper Cab)	Payload	1781	5660	10074	7388	23005
	Regulatory Permissible Weight	7100 7100 12000 8700 5319 1440 1926 1312	32000			
	Technically Permissible Weight	7100	7100	12600	10400	33000
3242S	Kerb Weight	4651	2398	1541	1179	9769
(High Roof Sleeper Cab)	Payload	2449	4702	11059	9221	23231
	Regulatory Permissible Weight	7100	7100	9500	8500	32000
	Technically Permissible Weight	8000	13400	13400	-	34000
3542	Kerb Weight	Permissible Weight	10221			
(Day Cab)	Payload	2411	11161	11161	-	23779
	Regulatory Permissible Weight	8000	9500	9500	8700 1312 7388 8500 10400 1179 9221 8500	26000
	Technically Permissible Weight	8000	13400	13400	-	34000
3548T (Low Roof Sleeper Cab)	Kerb Weight	5698	2239	2239	-	10177
	Payload	2302	11161	11161	-	23823
	Regulatory Permissible Weight	8000	9500	9500	-	26000

